

High-resolution Mapping and Backscatter Studies in Support of the Ripples DRI

Larry Mayer, Christian de Moustier, Barbara Kraft, and Brian Calder
Center for Coastal and Ocean Mapping
University of New Hampshire

Durham, NH 03824

Phone: (603) 862-2615 fax: (603) 862-0839 email: lmayer@cisunix.unh.edu

Award Number N00014-04-1-0624

<http://www.mbp.unh.edu> and <http://www.ccom.unh.edu>

LONG-TERM GOALS

The long-term goal of the RIPPLES DRI is to develop the ability to predict the geometry and evolution of seafloor morphology and in particular the presence or absence of ripples which have been shown to affect the sub-seafloor penetration of acoustic energy. Specific goals are to:

- 1- Measure and model ripple morphology and gradients on scales ranging up to kilometers
- 2- Understand the response of ripples to changes in wave and wave-current forcing
- 3- Measure and model rates of biological degradation (or production) of seafloor morphology
- 4- Measure and model effects of a distribution of grain-scale properties (e.g. size, density, cohesion) on ripple morphology
- 5- Understand the role of ripples in generating surface and subsurface sedimentary structures.

OBJECTIVES

In support of these long-term goals, the UNH-CCOM team has conducted ultra high-resolution, multi-frequency, multibeam mapping program in order to:

- 1- Establish the overall morphological context in the area of the RIPPLES DRI/SAX04 experiment (bathymetry and acoustic backscatter)
- 2- Establish the detailed distribution of ripples and other small-scale features throughout the experimental area, before the start of the experiment, immediately after deployment of the sensors, and at intervals during the experiment
- 3- Explore techniques for using the backscatter recorded by the multibeam sonar as a means to remotely identify seafloor properties including acoustic parameters, grain-size and biological components.

| Report Documentation Page | | | | Form Approved OMB No. 0704-0188 | |
|--|------------------------------------|-------------------------------------|---|---|---------------------------------|
| Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. | | | | | |
| 1. REPORT DATE 30 SEP 2005 | | 2. REPORT TYPE | | 3. DATES COVERED 00-00-2005 to 00-00-2005 | |
| 4. TITLE AND SUBTITLE High-resolution Mapping and Backscatter Studies in Support of the Ripples DRI | | | | 5a. CONTRACT NUMBER | |
| | | | | 5b. GRANT NUMBER | |
| | | | | 5c. PROGRAM ELEMENT NUMBER | |
| 6. AUTHOR(S) | | | | 5d. PROJECT NUMBER | |
| | | | | 5e. TASK NUMBER | |
| | | | | 5f. WORK UNIT NUMBER | |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of New Hampshire, Center for Coastal and Ocean Mapping, Durham, NH, 03824 | | | | 8. PERFORMING ORGANIZATION REPORT NUMBER | |
| 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) | | | | 10. SPONSOR/MONITOR'S ACRONYM(S) | |
| | | | | 11. SPONSOR/MONITOR'S REPORT NUMBER(S) | |
| 12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited | | | | | |
| 13. SUPPLEMENTARY NOTES code 1 only | | | | | |
| 14. ABSTRACT | | | | | |
| 15. SUBJECT TERMS | | | | | |
| 16. SECURITY CLASSIFICATION OF: | | | 17. LIMITATION OF ABSTRACT Same as Report (SAR) | 18. NUMBER OF PAGES 9 | 19a. NAME OF RESPONSIBLE PERSON |
| a. REPORT unclassified | b. ABSTRACT unclassified | c. THIS PAGE unclassified | | | |

APPROACH

At the crux of the RIPPLES DRI/SAX04 program is a multi-disciplinary experiment involving the deployment of a number of acoustic sensors in a small area off the coast of Destin, FL. The area selected is the site of the SAX99 experiment, an approximately 1 km² area with water depths of approximately 18 – 20 m located off the Florida Panhandle (with an extension to deeper water for the DRI program). In support of these efforts, and in order to address our specific objectives, we conducted a series of multibeam sonar surveys of the RIPPLES DRI/SAX04 experiment site that serve multiple purposes. First and foremost, these surveys place the entire experiment in a morphological and lithological context that allows investigators to understand the local bottom relief spectra and sediment distribution over spatial scales ranging from a few kilometers to a few centimeters. At the same time, we provide investigators with the regional (100's to 1000's of meters) distribution of the bathymetry and sediment distribution but with the same level of resolution (10's of centimeters). In addition to addressing questions of ripple morphology and distribution over many scales, we also hope to use the multibeam sonar(s) to determine the acoustic backscatter response of a rippled seafloor over a wide range of angles and under a number of conditions.

The surveys were conducted on a 46' Naval Oceanographic Office (NAVOCEANO) hydrographic survey launch (HSL) that is based in Gulfport, MS and equipped with precision navigation equipment and two state-of-the-art dynamically focused multibeam sonars (a 300 kHz – 130 degree, Simrad EM3002, and a 455 kHz, 120 degree, Reson 8125 – the same sonar we used to resolve ripples and mines off Martha's Vineyard, MA). Both systems collect backscatter as a function of beam angle but in the configurations we are using, only the Simrad system provides a full time series of backscatter values across each beam footprint. The Reson system provides a single average value of backscatter for each beam (thus much lower resolution) or a full time series of backscatter values across the swath with no angular resolution (e.g. standard sidescan sonar). Constraints on the survey were the inability of the NAVOCEANO vessel to work in water shallower than 5 meters and the need for significant overlap of one swath with the next in order to ensure high-resolution. Also, to ensure high quality data and dense data coverage in the along-track direction, survey speeds were kept below 6 knots.

Funding was available for approximately 20 days of survey work through the course of the experiment. We proposed to divide these into 5, 4-day survey blocks so that we may examine both the short and long-term temporal and spatial variations of the ripples with respect to the local environmental conditions. We proposed to spread 4 of the survey blocks over the time period between early Sept. and mid Nov. and save one of the surveys for an "event response" – a survey conducted directly after a storm event. In planning our survey work we tried to meet the objectives of the RIPPLES DRI, the SAX04 investigators, as well as Naval Research Laboratory (NRL) researchers who are studying coastal processes at an area (known as the TOWER Site) near the RIPPLES DRI/SAX04 experiment and who are contributing to the cost of the field work.

Detailed Survey Plan (Figure 1):

SAX04 Site – an approximately 2 km (EW) by 1 km (NS) box centered around (but slightly offset from) the R/V Seward Johnson and the buried target site. The survey box starts at approximately the 5 m contour and extends about 1 km offshore from there (to a depth of approximately 18 – 19 m). An area of this size can be fully surveyed with ripple-resolving resolution in approximately one day.

TOWER Site – an approximately 3 km (EW) by 600 m (NS) box directly offshore the coastal meteorology tower. This survey will start at the 5 m contour and continue about 600 m offshore (to approximately the 15m contour). A full coverage, high-resolution survey in this area takes about one day.

SAX04 Deepwater Lines (DRI Survey) – The RIPPLES DRI objectives call for surveys out to 25 – 30 m depth. It is impossible to get full coverage over an area this large in the time available so we ran a series of individual NS lines about 10 km long running from the southern boundary of the SAX04 survey box to approximately 25 – 27 m depth. These lines have a swath width of about 2 times the water depth and thus average about 40 m wide.

TOWER Site Deepwater Lines – NRL requested survey data further offshore but only to 18 m depth.




Figure 1: Overview of RIPPLES DRI/SAX04 surveys bathymetric map of region offshore of Destin, FL showing the 1×2 km detailed area for the SAX04 survey, the 10 km long, NS Deepwater Lines for the DRI survey, and the 3 km by 600 m detailed TOWER survey area.

Along with our bathymetric mapping objectives we also hoped to continue our research into the potential role that multibeam sonar backscatter measurements can play in the remote identification of seafloor properties. As described in Fonseca *et al.* (2002), we have been working with the composite roughness model of Jackson *et al.* (1986) to see how it can be applied to the analysis of multibeam sonar data. In the context of Fonseca *et al.*, we modified the model to explore the role of gassy in sediments and used this modified model to analyze multibeam sonar data from the Eel River margin. We have continued this work with the development of an interactive tool that is modeled after AVO (Amplitude Versus Offset) analyses that are standardly done in offshore petroleum exploration. The tool automatically ingests multibeam sonar bathymetry and backscatter data, makes all corrections

necessary (including corrections for local slope) to calculate true backscatter, and then allows a constrained (by Hamilton physical property inter-relationships) iterative process that adjusts model input parameters (seafloor properties) until they best fit various pre-defined portions of the measured backscatter vs. angle of incidence data (Fonseca, Mayer, and Kraft, 2005 – see Geoclutter Progress Report).

WORK COMPLETED

The first of the scheduled surveys (the pre-deployment survey) was conducted between 31 August and 3 September 2004 with both a Reson 8125 and Simrad EM3002 multibeam echosounder using the NAVOCEANO HSL *Bertram*. The SAX04 Site, the DRI Deepwater Lines (nine), and the TOWER Site were mapped, collecting 120 Gbytes of data in 4 days. Preliminary bathymetric maps were produced within a few days of the survey work and provided to the SAX04 and DRI teams. This initial survey produced a base map from which comparisons to future surveys can be made.

Scheduling of the remaining surveys was hampered considerably due to Hurricane Ivan which made landfall (near Gulf Shores, AL) on 16 September 2004. Hurricane Ivan, although viewed by some as opportunistic for the RIPPLES DRI/SAX04 experiment, caused extensive damage to the Pensacola area. Tentative plans for an “event response” survey to commence on 4 October were completed but were eventually cancelled due to logistical challenges. The US Coast Guard (USCG) Station at Destin, which had agreed to provide docking space for the HSL during the nighttime hours of all surveys, was damaged and without power. All efforts to secure alternate dock space failed. The second survey was rescheduled to begin in mid-October. Just prior to this date, the HSL encountered serious engine problems and underwent repairs in Panama City.

The second survey was eventually conducted between 25-29 October 2004, nearly six weeks post Hurricane Ivan and thus could no longer be considered an “event response” survey. The HSL was permitted to dock at the USCG Station pier which remained without power. A survey plan similar to the first survey was followed with the R/V Seward Johnson remaining moored in the SAX04 site (see Fig. 2) during the survey. A smaller area of the TOWER site, approximately 350 m (NS), was mapped due to the presence of nearly 1.6 meters of fine sand in the northern area of the survey box (see Fig. 4). The Reson 8125 bathymetry data from both surveys and all sites (SAX04, TOWER, and Deepwater Lines) has been processed. The EM3002 data from the SAX04 and TOWER sites has also been processed for acoustic backscatter.

A third survey was scheduled for 13-16 December 2004 but had to be cancelled due to a recurrence of the engine problems on the HSL. To date the HSL is still not available for survey work.

RESULTS

Shown in Figure 2 is Reson 8125 bathymetry of the SAX04 experiment site from the (a) first and (b) second surveys. The first survey was completed after mine-like targets had been buried in the area bounded by large clump weights (four objects proud on the seafloor). The second survey occurred while the SAX04 experiment was in full-swing. In Figure 2(b), yellow circles outline the location of the R/V Seward Johnson moorings, which remained moored during the multibeam survey. No ripples were observed in the bathymetric data from the first survey, within the vertical resolution of the sonar (< 5 cm). Some small-scale features are present in the bathymetry from the second survey, however

most of the ripples generated by Ivan had degraded by the time the survey was completed at the end of October.




Figure 2: Reson 8125 bathymetry of the SAX04 experiment site during the (a) first and (b) second surveys. In (a), the 2000-lb clump anchors located at each corner of the 60 m by 60 m buried target field are evident. In (b), the yellow circles outline the location of the R/V Seward Johnson moorings. Objects proud on the seafloor are deployed equipment associated with the SAX04 experiment. The large object approximately in the center of the area is the APL-UW rail system (30 m in length). Water depth near the SAX04 site was approximately 17 m.

Large-scale ripple features are present in the SAX04 Deepwater Lines bathymetric data from the second survey. Shown in Figure 3 is a small section of the NS lines that extends from approximately

19 to 24 m water depth. Long crested ripples are present with wavelengths on the order of 8 to 10 m and amplitudes of 10 to 15 cm.




Figure 3. Perspective view of deep-water (19-24 m) bathymetry from Reson 8125 multibeam sonar collected south of the SAX04 survey site (see Fig 1 for location). Bathymetry clearly shows E-W-oriented, long-crested ripples with wavelengths of 8 – 10 m and amplitudes of 10 -15 cm.

The most visible changes to the seabed following Ivan were observed in the TOWER site (see Fig. 1 for location). Shown in Figure 4 is the Reson 8125 bathymetry from the first (a) and second (b) surveys. A bathymetric difference map (in meters) between the two surveys is shown in (c). Following Ivan, nearly 1.6 m of fine sand was deposited in the northern region of the survey area. Fingers of fine sand, oriented perpendicular to the shoreline, extend across the region. The low backscatter fine sand overlaying the higher backscatter medium sand is shown in (d).




Figure 4: Reson 8125 bathymetry (in meters) of the TOWER site during the (a) first and (b) second surveys; (c) bathymetric difference (second survey bathymetry relative to first survey bathymetry, in meters); and (d) Simrad EM3002 backscatter from the second survey with low backscatter (dark color) and high backscatter (light color).

IMPACT/APPLICATIONS

The initial survey has served as a base map for other investigations and a means of quantifying roughness spectra over a range of spatial scales (see Briggs et al., 2005). The single repeat survey has helped quantify the major change in seafloor bathymetry and sediment distribution after Hurricane Ivan (albeit six weeks after the storm) but the inability to mount a quick “event” response and subsequent surveys have greatly reduced the effectiveness of the mapping program.

TRANSITIONS

Reson 8125 bathymetry of the TOWER and SAX04 sites has been transitioned to Dr. Todd Holland. Profiles of bathymetric data along several NS and EW lines within the SAX04 site and along the NS direction in the SAX04 Deepwater Lines have been transitioned to Dr. Kevin Briggs to complete bottom roughness spectra.

RELATED PROJECTS

Mine Burial and Uncertainty DRI's.

REFERENCES:

Fonseca, L., Mayer, L.A., and Kraft, B., 2005, Seafloor characterization through the application of AVO analysis to multibeam sonar data, in, Pace, N. and Blondell, P, eds., *Boundary Influences in High Frequency Shallow Water Acoustics*, Proceedings of the Institute of Acoustics, pp. 241-250.

Fonseca, L., Mayer, L., Orange, D., and Driscoll, N, “The high-frequency backscattering angular response of gassy sediments: Model/data comparison from the Eel River Margin, California,” *J. Acoust. Soc. Am.*, vol. 111, no. 6, pp. 2621-2631, 2002.

Jackson, D. R., Winebrenner, D. P. and Ishimaru, A., “Application of the composite roughness model to high-frequency bottom backscattering,” *J. Acoust. Soc. Am.*, vol. 79, no. 5, pp. 1410-1422, 1986.

PUBLICATIONS:

Briggs, K.B., Lyons, A.P., Pouliquen, E., Mayer, L.A., and Richardson, M., 2005, Seafloor roughness, sediment grain size and temporal stability, in, Papadakis, J.S. and Bjorno, L, eds. *Proceedings of the Intl. Conference on Underwater Acoustic Measurements: Technologies and Results*, Crete, Greece. ISBN: 960-88702-08